



**SOD-123 Plastic-Encapsulate Diodes****BAT42W/BAT43W****SCHOTTKY BARRIER DIODE****FEATURES**

- Fast Switching Speed
- Low Forward Voltage Drop

**MARKING**

| BAT42W                                                                            | BAT43W                                                                            |
|-----------------------------------------------------------------------------------|-----------------------------------------------------------------------------------|
|  |  |

**MAXIMUM RATINGS** ( $T_a=25^{\circ}\text{C}$  unless otherwise noted)


| Parameter                                             | Symbol          | BAT42W/BAT43W | Unit               |
|-------------------------------------------------------|-----------------|---------------|--------------------|
| Peak Repetitive Peak Reverse Voltage                  | $V_{RRM}$       | 30            | V                  |
| Working Peak Reverse Voltage                          | $V_{RWM}$       |               |                    |
| DC Blocking Voltage                                   | $V_R$           |               |                    |
| RMS Reverse Voltage                                   | $V_{R(RMS)}$    | 21            | V                  |
| Forward Continuous Current                            | $I_{FM}$        | 200           | mA                 |
| Repetitive Peak Forward Current @ $t<1.0s$            | $I_{FRM}$       | 500           | mA                 |
| Non-repetitive Peak Forward Surge Current @ $t=8.3ms$ | $I_{FSM}$       | 4.0           | A                  |
| Power Dissipation                                     | $P_D$           | 500           | mW                 |
| Thermal Resistance Junction to Ambient                | $R_{\theta JA}$ | 200           | /W                 |
| Operating Junction Temperature Range                  | $T_J$           | -40 ~ +125    | $^{\circ}\text{C}$ |
| Storage Temperature Range                             | $T_{STG}$       | -55 ~ +150    |                    |

**ELECTRICAL CHARACTERISTICS** ( $T_a=25^{\circ}\text{C}$  unless otherwise specified)


| Parameter                     | Symbol     | Min   | Typ  | Max  | Unit          | Conditions                                                |
|-------------------------------|------------|-------|------|------|---------------|-----------------------------------------------------------|
| Reverse breakdown voltage     | $V_{(BR)}$ | 30    |      |      | V             | $I_R=10\mu\text{A}$                                       |
| Forward voltage               | All Types  | $V_F$ |      | 1.0  | V             | $I_F=200\text{mA}$                                        |
|                               | BAT42W     | $V_F$ |      | 0.4  | V             | $I_F=10\text{mA}$                                         |
|                               | BAT42W     | $V_F$ |      | 0.65 | V             | $I_F=50\text{mA}$                                         |
|                               | BAT43W     | $V_F$ | 0.26 | 0.33 | V             | $I_F=2\text{mA}$                                          |
|                               | BAT43W     | $V_F$ |      | 0.45 | V             | $I_F=15\text{mA}$                                         |
| Reverse current               | $I_R$      |       |      | 0.5  | $\mu\text{A}$ | $V_R=25\text{V}$                                          |
| Capacitance between terminals | $C_T$      |       |      | 10   | pF            | $V_R=1.0\text{V}, f=1.0\text{MHz}$                        |
| Reverse recovery time         | $t_{rr}$   |       |      | 5    | ns            | $I_F=I_R=10\text{mA}$<br>$I_{rr}=0.1I_{R}, R_L=100\Omega$ |

## Typical Characteristics


### Forward Characteristics




### Reverse Characteristics




### Capacitance Characteristics



### Power Derating Curve




Package Outline Dimensions (SOD-123)



| Symbol | Dimensions In Millimeters |       | Dimensions In Inches |       |
|--------|---------------------------|-------|----------------------|-------|
|        | Min                       | Max   | Min                  | Max   |
| A      | 1.050                     | 1.250 | 0.041                | 0.049 |
| A1     | 0.000                     | 0.100 | 0.000                | 0.004 |
| A2     | 1.050                     | 1.150 | 0.041                | 0.045 |
| b      | 0.450                     | 0.650 | 0.018                | 0.026 |
| c      | 0.080                     | 0.150 | 0.003                | 0.006 |
| D      | 1.500                     | 1.700 | 0.059                | 0.067 |
| E      | 2.600                     | 2.800 | 0.102                | 0.110 |
| E1     | 3.550                     | 3.850 | 0.140                | 0.152 |
| L      | 0.500 REF                 |       | 0.020 REF            |       |
| L1     | 0.250                     | 0.450 | 0.010                | 0.018 |
| θ      | 0°                        | 8°    | 0°                   | 8°    |

Suggested Pad Layout (SOD-123)



- Note:
1. Controlling dimension: in millimeters.
  2. General tolerance:  $\pm 0.05\text{mm}$ .
  3. The pad layout is for reference purposes only.